

**LEGEND**

- GRADING LIMITS
- FILL
- CUT
- DESIGN CONTOUR (CONTOUR INTERVAL 0.2m)
- EXISTING CONTOUR (CONTOUR INTERVAL 0.2m)
- RETAINING WALL (REFER TO TYPICAL DETAILS ON DRAWING 21-000475-xxx)
- SWALE DRAIN
- TREE TO BE RETAINED
- TREE TO BE REMOVED
- TREE PROTECTION FENCE
- STAGE BOUNDARY
- ESTATE BOUNDARY
- CUTOFF DRAIN FOR CLEAR WATER DIVERSION
- CUTOFF DRAIN FOR CSG SITE RUNOFF


- NOTES**
1. PRIOR TO COMMENCING EARTHWORKS STRIP TOPSOIL FOR INSPECTION BY SUPERINTENDENT. HOLD POINT. SURFACE TO BE INSPECTED FOR PRE EXISTING FILL.
  2. SILTY SOILS UNDERLYING THE TOPSOIL IS TO BE REMOVED IN ROAD SUGRADES.
  3. GENERALLY DISTURBED AREAS ARE TO BE TOPSOILED UP TO 150mm THICKNESS WITH SITE TOPSOIL AND GRASSED. BLOCKS ARE TO BE TOPSOILED 200mm THICKNESS.
  4. FILL FROM EXCAVATIONS WHICH MEETS THE REQUIREMENT FOR CONTROLLED FILL SHALL BE PLACED ON BLOCKS TO THE FULL DEPTH OF FILL.
  5. STOCKPILES OF TOPSOIL ARE NOT TO BE LEFT ON COMPLETION OF WORKS.
  6. WHERE DIRECTED BY THE SUPERINTENDENT PLACE CONTROLLED FILL ON BLOCKS AND ORDINARY FILL IN ROAD RESERVES TO UTILISE ALL SURPLUS SPOIL MATERIAL FROM THE SITE.
  7. FILL ON BLOCKS SHALL BE CONTROLLED FILL PLACED TO LEVEL 1 CONTROL TO AS3598.

SURVEY PROVIDED BY  
DATE OF SURVEY

Plot Date: 8-Apr-22, 9:57 AM File: H:\21-000475-100475-D120.dwg User:Byju Mathew

FIRST ISSUE	DESIGN	DRAWN	CHECK	APPROVED	DATE
ARM	SM	AK	AK		08/04/2022

AMENDMENT DETAILS	



CANBERRA SAND AND GRAVEL, BLOCK  
1582 BELCONNEN

DISCLAIMER  
ALL DIMENSIONS TO BE CHECKED ON SITE BY CONTRACTOR  
PRIOR TO CONSTRUCTION. USE WRITTEN DIMENSIONS ONLY, DO NOT SCALE.

GRADING PLAN  
SHEET 1 OF 5  
21-000475 D120